



**G650V08 / G820V08 /
G1002V08 / G1260V08**

**G1002V08 / G1202V08 / G1382V08
G1602V08 / G1942V08 / G2572V08**
Shown with Hull Support Extensions



General Specification:

Hot dipped galvanised chassis, with adjustable galvanised sliding axle(s) for better balancing, EEC 94/20 approved coupling system, fully adjustable winch post (where fitted), Steel galvanised and painted mudguards, Multi-roller system adjustable for different hulls and are self aligning, lashing points, keel rollers (except certain models), adjustable length lighting board, protected lights, jockey wheel (most models).

Model	Gross Weight Kgs	Payload Kgs	Max Hull Length mtr.	Axles	Tyres	Price € (Incl. VAT)
G650V8	900	650	5.50	1	175/70 R13	€2,110.00
G820V08	1100	820	5.080	1	165 R14C	€2,330.00
SO1261		<i>Keel Support Extension Kit</i>				€200.00
G1000V08	1300	1000	6.00	1	165 R14C	€2,640.00
G1260V08	1600	1260	6.50	1	185/70 R14C	€3,010.00
SO1260		<i>Keel Support Extension Kit</i>				€200.00
G1202V08	1600	1200	6.70	2	165/70 R13	€3,250.00
SO1258		<i>Keel Support Extension Kit</i>				€210.00
G1382V08	1800	1380	6.90	2	175/70 R13	€3,400.00
G1602V08	2120	1600	7.20	2	185/70 R13	€3,810.00
G1942V08	2500	1940	7.50	2	165 R14C	€3,970.00
G2572V08	3200	2570	8.50	2	185/70 R14C	€5,100.00
SO1259		<i>Keel Support Extension Kit</i>				€260.00
S28019		<i>Brake Flush Kit (per axle)</i>				€50.00

Trailers over 750 Kgs gross will require Brakes
The Payload per trailer may vary depending on options fitted
The Manufacturer and their agents reserve the right to change the specifications and Prices without notice